

SCALP AQUA 03

CONCENTRATED DEGREASER AND DETERGENT, FOR SYNTHETIC,
MINERAL SURFACES USED IN BUILDING
FORMULA SPECIFICALLY ADAPTED FOR DEGREASING AND CLEANING SOLAR
PANELS



PRODUCT BENEFITS



- Strong degreasing power
- Highly versatile
- Fast action
- Highly concentrated, odourless, no rinsing required.



ALL SURFACES Does not affect building materials



PACKAGING:

- Drum of 200 L
- 20 L: pallet of 24 X 20 L
- 5 L: carton of 4 X 5 L
- 1 L: carton of 12 X 1 L
- 1 L SPRAY: carton of 12 X 1 L

A REAS OF APPLICATION

This product has been designed for the cleaning and degreasing of all synthetic surfaces met in buildings such as PVC, painted surfaces (paint detergent), aluminium profiles, zinc, brass, galvanized materials, and plastic tarpaulins. It is perfectly suitable for daily cleaning of tiled mineral surfaces, glazed stone finishes, etc. It can be used as an industrial detergent for mechanical parts, generator motors etc.

APPLICATION

- **1. DILUTION**: From 5 to 50% depending on the amount of grime and the surface treated.
- 2. TOOLS: Sponge, cloth, sprayer, high-pressure equipment, industrial washer. For use in high-pressure machinery, we advise a concentration of the order of 1 to 5% at lance point (according to the state of the surface). For soaking applications, soak parts in the product preferably heated to 70°C. Leave to act for about twenty minutes. Remove parts, brush and rinse under running water.
- 3. METHOD: Dilute the product before application. (See below). Apply the product with a sponge then wipe the surface dry with a cloth or cotton wool. No need to rinse.

4. APPLICATION TIME: Immediate.

Technical Data Sheet • Septembre 2023

- 5. APPLICATION TEMPERATURE: From 5 to 50°C. Efficacy is reduced at extreme temperatures.
- <u>6. CLEANING OF TOOLS</u>: Tools should be cleaned with water.
- 7. APPLICATION RATE: According to the dilution of the product.*
- 8. STORAGE: store the product in a cool dry place and out of direct sunlight.
- * Coverage areas are provided for information only and can be used to assess a project. They are in no way contractual; only tests can define the actual amount of product required depending on the surface to be treated.

PHYSICOCHEMICAL PROPERTIES

- Aqueous detergent
- Fluorescent yellow liquid
- Density: 1.06 +/- 0.03 g/cm3 at
 - 20°C
- pH: 10.5
- · Not frost resistant, but effect reversible
- Flash point : N/A

PPLICATION PRECAUTIONS

- 1. PROTECTION OF SURFACES: Does not present any particular dangers to materials.
- 2. PROTECTION OF PERSONS: Avoid contact with eyes and skin. In the event of contact, immediately wash with water. Wear PVC gloves.

Important: The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand. See the Safety Data Sheet (SDS).





