

DASHBOARD RESTORER

DASHBOARD RESTORER AND CLEANER. AVAILABLE IN MATT, SATIN OR GLOSS









- Long-lasting restorer.
- Frost-proof.
- Easy to use.
- Neutral pH.



PACKAGING:

- 1,000 L container
- 210 L barrel
- 20 L: 24 x 20 L pallet
- 5 L: 96 x 5 L pallet

A REAS OF APPLICATION

Scalp DASHBOARD RESTORER restores dashboards, plastics, vinyl, imitation leather and other imitation materials. It works immediately, protecting, cleaning and preserving surfaces, giving them a matt, satin or glossy, non-greasy finish.

APPLICATION

- **1.DILUTION**: Product is ready to use.
- **2.APPLICATION EQUIPMENT:** Sponge or cloth.
- **3.MODE OF OPERATION:** Apply evenly to the surface being cleaned, avoiding excess product. Works immediately.
- **4.APPLICATION TEMPERATURE**: 5 °C to 50 °C. Effectiveness is reduced at extreme temperatures.
- **5. TOOL CLEANING:** Clean tools with water straight after application.
- 6. YIELD: 50 ml / m².
- **7. STORAGE**: Store product in frost-free premises, away from the elements and direct sunlight. Do not store at temperatures < 5 °C.

Technical Data Sheet • June 2021 Page 1/2 * Yield information is only provided as a rough guide. This information is useful to determine the amount needed for the work. This information is in no way contractual. The exact quantity of product to be applied can only be established through tests, based on the different surfaces to be treated.

PHYSICO-CHEMICAL FEATURES

Restorer

pH: 7

Colourless liquid

Frost-proof

Density: 1.0 g / cm3 at 20 °C

Flash point: None

APPLICATION PRECAUTIONS

- 1. PROTECTION OF SURFACES: Do not apply product to surfaces that are very hot or have been exposed to the sun.
- 2. PROTECTION OF PERSONS: Avoid contact with eyes. In the event of splashing, rinse with water.

Important: The contents of this document stem from our experience with the product. We cannot be held liable as far as its use is concerned in every individual case. Given the particular characteristics of each surface (wear and tear, alteration of the entire surface and/or its properties, chemical composition etc.), and to avoid any damage to the surface to be treated, it is essential that the Scalp product be tested on a small area to be treated, by following the procedure for application, in order to ensure that no alteration occurs.



