# STRIPPER RANGE

### **SCALPEX SD+**

HIGH PERFORMANCE GEL FACADE STRIPPER.
DOES NOT CONTAIN DCM OR NMP

# P PRODUCT BENEFITS



- Does not contain DCM
- Highly versatile
- Effective and fast in its category
- Non-drip (reduced consumption)
- Ideal viscosity adapted for vertical surfaces







### **PACKAGING**:

20 kg: pallet of 24 X 20 kg

# A REAS OF APPLICATION

This is an evolution of the product SCALPEX SD. This product with neutral pH is designed to strip building paints, thick and medium plasticized coatings, glues, inks, varnishes, from concrete, stone, brick, vitreous paste, wood, mineral sealers surfaces.

# APPLICATION

- 1. **DILUTION**: Ready to use.
- 2. APPLICATION EQUIPMENT: Brush in natural fibres, could be sprayed with an airless spray gun.
- 3. METHOD: Apply in a thick layer. Leave the product to act until total softening of the coating, then scrap and rinse the surface. Avoid applying to wet surfaces.
- 4. APPLICATION TIME:: From 15 mn to 1 h according to the coating.
- <u>5. APPLICATION TEMPERATURE</u>: From 2 to 45°C. Efficacy is reduced at extreme temperatures.
- 6. CLEANING OF TOOLS: Clean tools in preferably soapy water immediately after use.
- 7. APPLICATION RATE: About 700 ml / m<sup>2</sup> according to coating.\*
- **8. STORAGE :** Store the product in a frost-free location where it is protected from the weather and away from direct sunlight.
- \* Coverage areas are provided for information only and can be used to assess a project. They are in no way contractual; only tests can define the actual amount of product required depending on the surface to be treated.



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.

### PHYSICOCHEMICAL PROPERTIES

Solvent based product
 pH : 5 +/- 0.5

Milky gel
 Density: 0.97 +/- 0.03 g/cm³ at 20°C
 Viscosity: > 5000 cps
 Flash Point: 52 °C

## A PPLICATION PRECAUTIONS

<u>1. PROTECTION OF SURFACES</u>: Do not apply to PVC, rubber, plastic tiles, polystyrene.

**2. PROTECTION OF PERSONNEL:** Avoid contact with eyes and skin. In case of contact, immediately wash with water. Wear PVC gloves and protective eyewear. Do not inhale fumes. Keep away from combustible material.

**Important**: The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand. See the Safety Data Sheet (SDS).



