# SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.

## **SCALP CONSOLIDANT HYDROFUGE**

STRENGTHENING AND WATER-REPELLENT MINERALISING AGENT FOR STONE, BRICK AND MINERAL COATINGS.









- Does not alter surface qualities
- Very easy to work with
- Can be sprayed
- Does not modify water vapour permeability
- Two in one (time saved on site)



### **PACKAGING:**

- In drum of 200 L
- 30 L: pallet of 24 X 30 L
- 5 L : carton of 4 X 5 L



Penetrating liquid designed to strengthen by mineralising and water-repellent coating surfaces such as: lime and siliceous stones, brick, concrete, mineral coatings. Atmospheric pollution degrades facades and causes the elimination of their natural binding agents. This product mineralises and protects them against water penetration damage.

# APPLICATION

- 1. DILUTION: SCALP CONSOLIDANT HYDROFUGE is ready to the use, do not dilute..
- 2. Tools: Roller, low pressure sprayer.
- 3. METHOD: Mix SCALP CONSOLIDANT HYDROFUGE well. Apply SCALP CONSOLIDANT HYDROFUGE from the base upwards until saturation of the surface on a clean and dry surface in two coats at a minimum of 15 minutes interval.
- **4. APPLICATION TIME**: This is a permeating solution. It will be effective immediately after evaporation of solvents (after about 72 hours).
- <u>5. APPLICATION TEMPERATURE</u>: From 5 to 50°C. Efficacy is reduced at extreme temperatures.
- **6. CLEANING OF TOOLS**: Clean tools with white spirit immediately after use.
- 7. APPLICATION RATE: According to surface porosity.\*

8. STORAGE: Store the product in a frost-free location where it is protected from the weather and away from direct sunlight.

\* Coverage areas are provided for information only and can be used to assess a project. They are in no way contractual; only tests can define the actual amount of product required depending on the surface to be treated.

### PHYSICOCHEMICAL PROPERTIES

Solvented colourless liquid

Micro-porous

Density: 0.895 +/- 0.03 g /cm3 at

20°C

pH:7

Not frost resistant

Flash point: 34°C

# PPLICATION PRECAUTIONS

1. PROTECTION OF SURFACES: Protect surfaces that are not to be treated.

2. PROTECTION OF PERSONNEL: Avoid contact with eyes and skin. In case of contact, immediately wash with water. Wear PVC gloves and protective eyewear. Do not smoke. Do not inhale fumes.

Important: The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand. See the Safety Data Sheet (SDS).





