

SCALP MINERALISANT 95

HIGH PERFORMANCE WATER BASED STRENGTHENING
AGENT FOR STONE, BRICK, CONCRETE AND MINERAL
COATINGS.



P PRODUCT BENEFITS



- Very easy to work with
- Innovative product (water based)
- Does not alter surface qualities
- Can be sprayed
- Does not modify water vapour permeability
- Compatible with the water repellents :
SCALPFUGE PS 86, SCALPFUGE 35,
SCALPFUGE OM 70, SCALP ANTI-
TACHE 07



PACKAGING :

- In drum of 200 L
- 20 L: pallet of 24 X 20 L
- 5 L : carton of 4 X 5 L

A REAS OF APPLICATION

Penetrating liquid designed to strengthen by mineralising surfaces such as: lime and siliceous stones, brick, concrete, mineral coatings. Atmospheric pollution degrades facades and causes the elimination of their natural binding agents.

A PPLICATION

- 1. DILUTION:** SCALP MINERALISANT 95 is ready to the use, do not dilute.
- 2. TOOLS:** Roller, low pressure sprayer.
- 3. METHOD:** : Mix SCALP MINERALISANT 95 well. Apply SCALP MINERALISANT 95 from the base upwards until saturation of the surface on a clean and dry surface in two coats at a minimum of 15 minutes interval. Allow the surface to strengthen for about ten days before possible water repellent treatment. For badly degraded surfaces proceed with a new mineralising operation.
- 4. APPLICATION TIME:** This solution permeates the surface thoroughly.
- 5. APPLICATION TEMPERATURE:** From 5 to 50°C. Efficacy is reduced at extreme temperatures.
- 6. CLEANING OF TOOLS :** Clean tools in water immediately after use.



SCALP is a French family owned
business and manufacturer of
cleaning, protection and treatment
solutions, with over 65 years as a
construction-industry specialist.

8. STORAGE: Store the product in a frost-free location where it is protected from the weather and away from direct sunlight.

* Coverage areas are provided for information only and can be used to assess a project. They are in no way contractual; only tests can define the actual amount of product required depending on the surface to be treated.

PHYSICOCHEMICAL PROPERTIES

- | | |
|--|--|
| <ul style="list-style-type: none">• Colourless liquid• Micro-porous• Density : 1.02 +/- 0.03 g /cm³ at 20°C | <ul style="list-style-type: none">• pH : 9.5• Not frost resistant• Flash point : >80% |
|--|--|

APPLICATION PRECAUTIONS

1. PROTECTION OF SURFACES: Protect surfaces that are not to be treated.

2. PROTECTION OF PERSONNEL: Avoid contact with eyes and skin. In case of contact, immediately wash with water. Wear PVC gloves and protective eyewear.

Important: The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand. See the Safety Data Sheet (SDS).



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.

Technical Data Sheet • May 2021
Page 2/2