

## SCALP PRIMAFIX

HIGH PERFORMANCE WATER-BASED STRENGTHENING  
AGENT FOR PLASTER, STONE, BRICK, CONCRETE AND  
MINERAL COATINGS.



### PRODUCT BENEFITS



- New generation product
- Can be sprayed
- Water-based product
- Very easy to work with
- Ideal for the inside and the outside
- Changes neither the appearance nor the porosity of the surface.
- Better coating adhesion



### PACKAGING :

- 20 L: pallet of 24 X 20 L
- 5 L: carton of 4 X 5 L

### AREAS OF APPLICATION

SCALP PRIMAFIX is a permeating solution designed to strengthen surfaces brittle, friables and powdery such as plaster, mineral coating, lime and siliceous stones brick, concrete. Ideal for indoor or outdoor before new paint, wallpapers, tiles.

### APPLICATION

- 1. DILUTION:** SCALP PRIMAFIX is ready to use, do not dilute.
- 2. TOOLS:** Roller, low pressure sprayer.
- 3. METHOD:** Mix SCALP PRIMAFIX well. Apply SCALP MINERALISANT 95 from the base upwards until saturation of the surface on a clean and dry surface in two coats at a minimum of 1 hour ( $T^{\circ}C > 20^{\circ}C$ ) interval. Allow the surface to strengthen for about 24 hours before possible coating treatment. For badly degraded surfaces, proceed with a new mineralising operation.
- 4. APPLICATION TIME:** This solution permeates the surface thoroughly.
- 5. APPLICATION TEMPERATURE:** From 5 to  $50^{\circ}C$ . Efficacy is reduced at extreme temperatures.
- 6. CLEANING OF TOOLS :** Clean tools in water immediately after use.



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.

**7. APPLICATION RATE:** From 140 to 160 ml / m<sup>2</sup> per coat, according to surface porosity.\*

**8. STORAGE:** Store the product in a frost-free location where it is protected from the weather and away from direct sunlight.

\* Coverage areas are provided for information only and can be used to assess a project. They are in no way contractual; only tests can define the actual amount of product required depending on the surface to be treated.

## PHYSICOCHEMICAL PROPERTIES

- |  |  |
|--|--|
| <ul style="list-style-type: none"><li>• Water-based product</li><li>• Milky liquid</li><li>• Density : 1.02 +/- 0.03 g /cm<sup>3</sup> at 20°C</li></ul> | <ul style="list-style-type: none"><li>• pH : 4.4</li><li>• Not frost resistant</li><li>• Flash point : N/A</li></ul> |
|--|--|

## APPLICATION PRECAUTIONS

**1. PROTECTION OF SURFACES:** Protect surfaces that are not to be treated.

**2. PROTECTION OF PERSONNEL:** Avoid contact with eyes and skin. In case of contact, wash with water. Wear PVC gloves and glasses for ceiling use.

**Important:** The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand. See the Safety Data Sheet (SDS).



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.

Technical Data Sheet • May 2021  
Page 2/2