

## SCALP RENOV'EXPRESS

NEW CONCEPT EXTREMELY POWERFUL CLEANER DESIGNED FOR THE COMBINED REMOVAL OF MARKS OF ATMOSPHERIC AND VEGETAL ORIGIN.



### PRODUCT BENEFITS



- Time saving
- Thixotropic gel ideal for vertical surfaces
- Rapid action
- Product requiring no special labelling
- Strong action (removes blackening from atmospheric pollution)



### PACKAGING :

- In containers of 200 litres
- 20 litres: pallet of 24 X 20 litres
- 5 litres: carton of 4 X 5 litres

### AREAS OF APPLICATION

SCALP RENOV'EXPRESS is ideal for treating roofs, façades, walls, terraces and floors. SCALP RENOV'EXPRESS is designed for use on building materials (tile, slate, fibro-cement, shingle, stone, mineral coatings, brick, concrete, roughcast, thick plasticized coatings, wood). SCALP RENOV'EXPRESS allows the elimination in a single operation all kind of blackening from atmospheric pollution.

### APPLICATION

**1. DILUTION:** SCALP RENOV' EXPRESS is ready to use.

**2. TOOLS:** Equipment in nylon or synthetic fibre: Roller, brush, paintbrush. Can be sprayed with appropriate equipment: manual or electric sprayer and airless spray gun (contact our Sales Department).

**3. METHOD:** Mix SCALP RENOV' EXPRESS well then applies to the surface, from the base upwards. Allow to act for 2 to several hours then rinse fully with water under pressure from base upwards. Renew the operation if necessary.

**4. APPLICATION TIME:** Two to several hours according to the degree of pollution..

**5. APPLICATION TEMPERATURE:** From 5 to 50°C. Effectiveness is reduced at extreme temperatures.



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.

**6. CLEANING OF TOOLS :** Clean tools in water immediately after use.

**7. APPLICATION RATE:** From 150 to 250 ml /m2 environ.\*.

**8. STORAGE :** Store the product in a frost-free location where it is protected from the weather and away from direct sunlight.

\* Coverage areas are provided for information only and can be used to assess a project. They are in no way contractual; only tests can define the actual amount of product required depending on the surface to be treated.

## PHYSICOCHEMICAL PROPERTIES

- Sodium Hypochlorite based aqueous product
- Yellowish liquid
- Density : 1.16 +/- 0.03 g /cm<sup>3</sup> at 20°C
- pH : >13
- Not frost resistant
- Flash point : N/A

## APPLICATION PRECAUTIONS

**1. PROTECTION OF SURFACES:** Protect zinc, aluminium, galvanised materials, copper, surrounding vegetation.

**2. PROTECTION OF PERSONS:** This is a corrosive product. Wear appropriate protective equipment and clothing. Avoid contact with skin and eyes. Wash immediately and abundantly with water in case of contact. Do not inhale fumes and do not mix with acids. Do not pour the product or its waste into rivers or watercourses.

**Important:** The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand. See the Safety Data Sheet (SDS).



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.

Technical Data Sheet • May 2021  
Page 2/2