AUTOMOTIVE RANGE

SCALP TYRE'RENOV

TYRE AND RUBBER RESTORER

τορ

QUALITY



PRODUCT BENEFITS

- Long-lasting restorer.
- Frost-proof.
- Easy to use.
- Neutral pH.



- 1,000 L container
- 210 L barrel
- 20 L: 24 x 20 L pallet
- 5 L: 96 x 5 L pallet

AREAS OF APPLICATION

SCALP TYRE'RENOV is specially designed to give a fresh new look to tyres and rubber. It preserves and protects materials, even after their use, leaving a glossy, non-greasy finish.

APPLICATION

1.DILUTION: Product is ready to use.

2.APPLICATION EQUIPMENT: Sprayer or cloth.

<u>3.MODE OF OPERATION</u> : Apply evenly to a clean and dry surface, avoiding excess product. Leave to dry for a few minutes before using the vehicle.

<u>4.APPLICATION TEMPERATURE</u>: 5 °C to 50 °C. Effectiveness is reduced at extreme temperatures.

5. TOOL CLEANING: Clean tools with water straight after application.

6. YIELD: 50 ml / m²

<u>7. STORAGE</u>: Store product in frost-free premises, away from the elements and direct sunlight. Do not store at temperatures < 5 °C.

* Yield information is only provided as a rough guide. This information is useful to determine the amount needed for the work. This information is in no way contractual. The exact quantity of product to be applied can only be established through tests, based on the different surfaces to be treated.

Technical Data Sheet • May 2021 Page 1/2



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.



PHYSICO-CHEMICAL FEATURES

•

•

- Restorer
- Colourless liquid
- Density: 1.07 g / cm3 at 20 °C
- pH: 7 Frost-proof Flash point: None



<u>1. PROTECTION OF SURFACES</u>: Do not apply product to surfaces that are very hot or have been exposed to the sun.

<u>2. PROTECTION OF PERSONS</u>: Avoid contact with eyes. In the event of splashing, rinse with water.

Important: The contents of this document stem from our experience with the product. We cannot be held liable as far as its use is concerned in every individual case. Given the particular characteristics of each surface (wear and tear, alteration of the entire surface and/or its properties, chemical composition etc.), and to avoid any damage to the surface being treated, it is essential that the Scalp product be tested on a small area to be treated, by following the procedure for application, in order to ensure that no alteration occurs.



