

SUPRA BODYWORK


HIGHLY-CONCENTRATED VEHICLE BODY SHAMPOO

QUALITY -



P PRODUCT BENEFITS

- Does not leave streaks when rinsed.
 - Frost-proof.
 - Easy to use.





PACKAGING:

- 1,000 L container
- 210 L barrel
- 20 L: 24 x 20 L pallet
- 5 L: 96 x 5 L pallet



AREAS OF APPLICATION

Scalp SUPRA BODYWORK is recommended for cleaning vehicle bodies without mechanical action. It removes static film (road film) and also works on insect and diesel-fuel marks.

Can be used for cleaning heavy goods vehicles (side panels, covers and tarpaulins, bodywork etc.).

Thanks to its powerful cleaning action and high concentration of surfactants, SUPRA BODYWORK helps bring shine to surfaces.

APPLICATION

1.DILUTION: 2 % to 10 %

2.APPLICATION EQUIPMENT: Sprayer.

- 3.MODE OF OPERATION: a) Manual cleaning: apply by spraying from top to bottom onto the vehicle body. Leave to work for a few minutes, then rinse off with pressurised water while scrubbing with a synthetic or natural-fibre brush. Never let product dry.
- b) <u>For use in car-wash arches</u>: place product in the shampoo compartment of the arch, for it to be pumped and sprayed onto the whole vehicle by the boom nozzles provided for this purpose. Never let product dry. Rinse thoroughly with water.

4.APPLICATION TEMPERATURE: 5 °C to 50 °C. Effectiveness is reduced at extreme temperatures.

5. TOOL CLEANING Clean tools with water straight after application.

6. YIELD: 50 ml of pure product per 10 m².

7. STORAGE: Store product in frost-free premises, away from the elements and direct sunlight. Do not store at temperatures < 5 °C.

* Yield information is only provided as a rough guide. This information is useful to determine the amount needed for the work. This information is in no way contractual. The exact quantity of product to be applied can only be established through tests, based on the different surfaces to be treated.

| PHYSICO-CHEMICAL FEATURES | |
|---|--|
| Smell: pleasant Colourless to yellow-coloured liquid Density: 1.05 g / cm3 at 20 °C | pH: 5Keep from freezingFlash point: None |

PPLICATION PRECAUTIONS

1. PROTECTION OF SURFACES: Do not apply product to surfaces that are very hot or have been exposed to the sun. Do not let product dry on the vehicle body. 2. PROTECTION OF PERSONS: Wear gloves and safety goggles. Avoid contact with eyes. In the event of splashing, rinse with water.

Important: The contents of this document stem from our experience with the product. We cannot be held liable as far as its use is concerned in every individual case. Given the particular characteristics of each surface (wear and tear, alteration of the entire surface and/or its properties, chemical composition etc.), and to avoid any damage to the surface being treated, it is essential that the Scalp product be tested on a small area to be treated, by following the procedure for application, in order to ensure that no alteration occurs.



