

VERNACRYL 30

ANTI-GRAFFITI FILM PROTECTION RENEWABLE
(SACRIFICIAL) - ACRYLIC RESIN AND P.T.F.E. BASE IN
AQUEOUS PHASE (MATT OR GLOSS FINISH)



P PRODUCT BENEFITS



- Sophisticated product
- Insaponifiable
- Does not modify water vapour permeability.
- Matt or gloss finish
- Does not require a primer
- Does not yellow the surface
- Single component product
- Suitable for outside and inside
- Very high resistance to U.V., inks, felt pens, paint,
- Colourless



PACKAGING :

- 20 kg : pallet of 24 X 20 kg
- 5 kg : carton of 4 X 5 kg

A AREAS OF APPLICATION

VERNACRYL 30 is designed for bare surface protection such as: stones, bricks, concrete, cement wood, hydraulic coatings, against graffiti of all types (paints, felt pens, ink, etc.).

A APPLICATION

- 1. DILUTION:** Ready to use.
- 2. TOOLS:** Roller, airless spray gun.
- 3. METHOD:** Mix VERNACRYL 30 well before application. Apply in two crossed coats without overusing at 4-hour intervals (the first layer should be dry).
Graffiti Removal: Graffiti can be removed in two ways: with hot water 90°C minimum under pressure (100 bar) or by using SCALPEX NW (see Technical Spec.). Both cleaning methods will remove the protection, which will therefore need to be renewed.
- 4. APPLICATION TIME:** Protection will be effective after about 72 hours (according to outside temperature)..
- 5. APPLICATION TEMPERATURE:** From 5 to 50°C. Efficacy is reduced at extreme temperatures.
- 6. CLEANING OF TOOLS :** Clean tools in water immediately after use.



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.

7. APPLICATION RATE: From 150 to 200 g/m² per coat according to surface porosity.*

8. STORAGE : Store the product in a frost-free location where it is protected from the weather and away from direct sunlight.

* Coverage areas are provided for information only and can be used to assess a project. They are in no way contractual; only tests can define the actual amount of product required depending on the surface to be treated.

CARACTERISTICAS FISICOQUIMICAS

- | | |
|---|--|
| <ul style="list-style-type: none">• Aqueous emulsion• Milky liquid• Density: 1.05 +/- 0.03 g/cm³ at 20°C | <ul style="list-style-type: none">• pH : 8• Not frost resistant• Flash point : N/A |
|---|--|

APPLICATION PRECAUTIONS

1. PROTECTION OF SURFACES: Does not require any protection, clean possible splashes quickly with a cloth.

2. PROTECTION OF PERSONNEL: Avoid contact with eyes and skin. In case of contact, wash with water. Wear PVC gloves and protective eyewear.

Important: The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand. See the Safety Data Sheet (SDS).



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.

Technical Data Sheet • May 2021
Page 2/2