

SCALP AQUA 1000

DEGREASING DETERGENT SOLUTION IN AQUEOUS BASE FOR PREPARATION BEFORE PAINTING.
DEGREASER, CONCENTRATED DETERGENT



PACKAGING:

- In container de 1000 L
- In casks de 200 L
- In 20 L



A REAS OF APPLICATION

This product has been designed for the cleaning and degreasing of all synthetic surfaces encountered in the building such as facade cladding, PVC, painted surfaces (painter's laundry), aluminum, zinc, brass, galva, stainless steel, plastic sheeting. It is perfect for daily cleaning of mineral surfaces such as tiles, stoneware, marble, etc. and can be used in industrial detergency (auto washers etc.) for mechanical parts, engine generators etc.

APPLICATION

- **1. DILUTION:** Can be used pure or diluted from 5 to 50% depending on the fouling and the support.
- **2. APPLICATION EQUIPMENT**: Sponge, cloth, sprayer, high pressure material, auto washer. For use in a high-pressure machine, it is advisable to have a concentration of about 1 to 5% at the lance outlet (depending on the state of the surface). For dipping application, soak the pieces in the product preferably heated to 70 ° C. Leave on for about twenty minutes. Take out the pieces, brush and rinse under running water.
- 3. PROCEDURE: Dilution of the product before application (see above). Apply the product to the sponge on the support then wipe with a cloth or wipe. No need to rinse.
- 4. APPLICATION TIME: Immediate.
- **5.** APPLICATION TEMPERATURE: From 5 ° C to 50 ° C. At extreme temperatures, efficiency is reduced.

6. CLEANING THE TOOLS: The tools must be cleaned with water.

7. YIELD: According to the dilution of the product.

8.STORAGE:

Min storage temperature: +10 ° CMax storage temperature: + 25 ° C

Store in tightly closed containers, protected from the weather and direct sunlight.

If the product is not used within 12 months from the date of manufacture but storage conditions have been met then additional time may be allocated. In this case, contact our sales department.

PHYSICOCHEMICAL PROPERTIES

- Liquid detergent
- Light yellow liquid
- Density to 20°C: 1.05 +/-0,05
 g/cm³
- ph: 14
- Fear frost but reversible
- Flash point : none

A PPLICATION PRECAUTIONS

1. PROTECTION OF SURFACES: Do not apply pure on plastic surfaces.

2. PROTECTION DES PERSONNES : It is advisable to wear gloves and goggles. In case of splashing on the eyes and skin, wash with water. Prohibit all contact with skin or mucous membranes. Handle avoiding projections. For safe use, consult the safety data sheet.

Important: The content of this documentation is the result of our product experience. It can not engage our responsibility for its use in each particular case. It is also essential to carry out preliminary tests. Consult the Material Safety Data Sheet (MSDS)



