

## **SCALPIK L 16 NG**

COLD PICKLING STRIPPER FOR PICKLING BATH. WITHOUT METHYLENE CHLORIDE AT BASIC PH





## **PACKAGING:**

- IBC PEHD 1000l container, UN approved
- PEHD 200l blue plastic bin, UN approved
- PEHD 20I blue plastic jerrycan, UN approved

## REAS OF APPLICATION

SCALPIK L16 NG is a pickling solution specially designed for pickling varnishes and paints on wood.

This innovative product is free of chlorinated solvent and is a perfect replacement for liquid methylene chloride paint pickling supports.



**DILUTION**: Ready to use, do not dilute.

**APPLICATION EQUIPMENT:** in a pickling bath.

OPERATION METHOD: Fill the bath with SCALPIK L16 NG. Soak the pieces to be subjected to the pickling solution in the bath. Leave the pieces in the bath until full pickling of all paint layers. Take out the parts and rinse with pressurised

APPLICATION TIME: the time required for complete pickling varies from one to several hours.

**APPLICATION TEMPERATURE:** room temperature.

YIELD: about 100 g/m<sup>2</sup> depending on the nature of the paint to be subjected to the pickling solution.

ADVICE: it is strongly recommended to aerate the workplaces in order to evacuate the residual vapours.

**CLEANING THE TOOLS:** the tools must be cleaned with water. STORAGE:

Min storage temperature: + 5 ° C

Max storage temperature: + 25 ° C

Store in tightly closed containers, protected from the weather and direct sunlight.

If the product is not used within 12 months from the date of manufacture but storage conditions have been met then additional time may be allocated. In this case, contact our sales department.

## PHYSICOCHEMICAL PROPERTIES

- Product based on specific solvents
- Density to 20°C: 0.95 +/-0,05 g/cm<sup>3</sup>
- dark yellow liquid

- Ph: 14
- Flash point: 21° C
- Non-freezing



PROTECTION OF THE SUPPORT: it may have adverse effects on copper, aluminium and zinc.

PROTECTION OF PERSONS: Corrosive product. Take precautions when using chemicals. Avoid contact with eyes and skin. No smoking. Wear gloves and goggles. Make sure to work in a ventilated room. Keep the product away from sources of heat and ignition. Do not add water to the product. Do not add water to the bath containing SCALPIK L16 NG. Handle by avoiding splashing. For safe use, consult the safety data sheet.

Important: The content of this documentation is the result of our product experience. It can not engage our responsibility for its use in each particular case. It is also essential to carry out preliminary tests. Consult the Material Safety Data Sheet (MSDS)







