

SCALP ANTI - POUSSIÈRE

CONSOLIDATING AND WATER-REPELLENT IMPREGNATING AGENT

FOR POROUS, ABSORBENT AND SANDY SURFACES

• **Application area:**

- SCALP ANTI-POUSSIÈRE is used to waterproof, impregnate and seal porous, absorbent and sandy surfaces such as concrete, screeds and mineral substrates.
- SCALP ANTI-POUSSIÈRE is an innovative one-component water-based liquid with a siliceous binder. Typical applications:
 - surface protection for mineral building materials indoors and out, e.g. exposed concrete surfaces, parking decks, brick facades, concrete floors, precast concrete elements, tiles, interlocking paving stones, garden slabs,
 - for areas exposed to high mechanical and chemical wear, including salt water,
 - agricultural areas, wastewater areas, - protection against contamination of all kinds (algae, moss, graffiti - prevents deep penetration of paint into the substrate).

• **Application :**

- 1.** The surface to be treated must be solid, dry and dust-free. Remove loose parts, oil, grease and other contaminants. Make sure the surface is sufficiently dry before applying SCALP ANTI-POUSSIÈRE.
- 2.** Apply to absorbent, dry substrates by spray, brush or roller, covering the entire surface.
- 3.** Depending on absorbency, apply the product 2 times if necessary, within 10 minutes when the first application is still wet. 24 hours after application.

• **Yield :**

Consumption depends on the porosity of the surfaces to be treated and amounts to approx. 150-400 ml/m². Determine exact consumption by means of a preliminary test application*.

• **Packaging :**

60L



BENEFITS

- Super consolidator
- Excellent water repellent
- Non-film-forming
- Solvent and VOC free
- Excellent chemical resistance
- Water vapor permeable

Important : The contents of this documentation are based on our experience with the product. We cannot be held responsible for its use in any particular case. In view of the specific characteristics of each surface (wear, alteration of completeness and/or properties, chemical composition, etc.) and to avoid any deterioration of the surface to be treated, it is essential to carry out a test application of Scalp on a small area to be treated, in accordance with the application procedure, to ensure that no alteration has occurred. Professional product: dangerous, observe safety precautions. Wear Personal Protective Equipment (PPE) and consult the Material Safety Data Sheet (MSDS).