## **SCALP PEEL-OFF**



## Application area:

- SCALP PEEL-OFF is a single-component product, ready to use, water-based, designed for temporary protection of all surfaces (walls, facades, joinery, furniture, etc.) for indoor use.
- Upon drying, a flexible and resistant peelable film is formed. Your surfaces are therefore insulated and protected against scratches, ambient air, various types of splashes, mortar, glue, paint, sparks, etc.
- It is a liquid protection intended to cover both porous and non-porous surfaces. The dry film allows the passage of light machinery due to its high resistance and elasticity.
- Once the work is completed, the film can be easily removed by stretching and leaves no residue or yellowing on white paints.

## · Application:

- **1-** Thoroughly mix the product, as it is ready to use.
- **2-** Apply the product to a clean, sound, and dry surface using a brush or an airless pump (minimum 5.19). The thickness of SCALP PEEL-OFF should be adjusted based on environmental conditions and the desired resistance.
- **3-** Once the work is completed, the protective film can be removed by stretching.

<u>DRYING TIME</u>: Approximately 4 to 6 hours depending on the temperature.

<u>CLEANING OF TOOLS</u>: The application equipment (airless, brush, or roller) must be cleaned with the mixture of WATER+SCALP PRONET (Dilute SCALP PRONET with 10% in water) before rinsing it with water immediately after use.

• Yields:

0.6 to 1 kg/m<sup>2</sup>

• Packaging:

5 and 20KG



## **PRODUCT ADVANTAGES:**

- Time and labor-saving compared to plastic protections.
- Easy and ultra-fast application.
- Suitable for multiple surfaces such as walls, floors, objects, etc.
- Water-based with a natural rubber base. Environmentally-friendly protection formulated from plantbased raw materials.
- Dries at room temperature in approximately 4 to 6 hours.
- No volatile organic compounds (VOCs).
- High resistance to abrasion.
- No yellowing of the surface after removal.
- Sprayable product.
- Contributes to waste reduction (waste classification: DIB).

The content of this documentation is based on our product experience. However, it cannot be held responsible for its use in each specific case. Considering the unique characteristics of each surface (wear and tear, alterations in integrity and/or properties, chemical composition, etc.), and to prevent any damage to the treated surface, it is essential to conduct a test of the Scalp product on a small area following the application procedure to ensure that no alterations occur.

This product is intended for professional use and can be hazardous. Please observe the necessary precautions while handling it. Wear appropriate Personal Protective Equipment (PPE), and consult the Technical Data Sheet as well as the Safety Data Sheet (SDS) before use.