SCALP WATERPROOF BARRIER



• Area of application:

- This fibrous paste dries to form a non-stick waterproofing membrane that covers cracks forming on roofs, terraces, gutters, cornices, piping, chimney bases, etc.
- Ideal for repairing cracks and reinforcing all types of joints. SCALP WATERPROOF BARRIER forms a watertight, elastic film on the vast majority of substrates (PVC, galvanized steel, iron, etc.) and does not require subsequent coating. Can be applied in all types of weather.
- A versatile, durable and resistant solution, offering waterproof and weatherproof protection. Its ease of application, ability to repair and reinforce, and resistance to environmental conditions make it an ideal choice for construction or renovation projects requiring effective, long-lasting protection.

SCALP WATERPROOF BARRIER

Application:

- 1 Ready-to-use product. Apply SCALP WATERPROOF BARRIER to a clean, dry substrate.
- 2 Clean the surface to be repaired of all dust, mud, greasy deposits, dead leaves, etc. Blot the surface dry, then apply the product directly.
- 3 Recoat if necessary after 12-24 hours, depending on outside temperature.

Drying time: 4H to the touch.

- Coverage:
- 1-1.5kg/m²
- Packaging:

750g and 5KG

PRODUCT ADVANTAGES

- Light- and weather-resistant
- Repairs cracks
- Reinforces joints
- Forms a watertight film on roofs, terraces, etc.
- High elasticity
- Ready-to-use product
- Recoatable product
- Ideal for exterior use
- Non-sticky