

SCALP ACRYL BETON

COLORLESS CONCRETE GLAZE

PROTECTION AGAINST WATER INFILTRATION AND SOILING



P PRODUCT BENEFITS



- Water-repellent: protects against water, oil and stains
- Weather- and UV-resistant
- Fast-drying
- Easy concrete maintenance
- Allows substrate to breathe
- Colorless protection
- Cleaning-resistant protection



PACKAGING :

- In containers of 1000 litres
- In containers of 210 litres
- 20 litres: pallet of 24 X 20 litres

A AREAS OF APPLICATION

SCALP ACRYL BETON effectively protects new and old concrete against water and oil infiltration, stains and dirt. SCALP ACRYL BETON is a non-film-forming product that provides long-lasting protection against damage caused by stains and dirt of all kinds, atmospheric pollution, seepage, grease, etc. This concrete glaze ensures cleanliness of treated surfaces.

A APPLICATION

1. DILUTION:

- **IMPRINT COAT:** Dilute SCALP ACRYL BETON with a maximum of 20% water.
- **INTERMEDIATE AND FINISH COAT:** Homogenize well before application. Carry out a test application before applying the product.

2. TOOLS:

Roller, brush

3. METHOD:

- Before applying the product, ensure that the concrete substrate is clean, dry, sound and solid.
- **IMPRINT COAT:** Print the substrate with the product diluted with a maximum of 20% water.
 - **INTERMEDIATE AND FINISH COAT:** Apply an intermediate and top coat of undiluted SCALP ACRYL BETON.

Drying At 20°C And 65% Relative Humidity :

- Approx. 1 hour: dust-free
- Approx. 6 hours: rain-resistant
- Approx. 12 hours: recoatable



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.

4. APPLICATION TEMPERATURE: Air, substrate and product temperature: between +5°C and +35°C. Humidity < 80%. Do not apply in direct sunlight.

5. CLEANING OF TOOLS : Clean tools in water immediately after use.

6. APPLICATION RATE:

- **IMPRESSION COAT:** approx. 110-210ml/m² diluted product*.
- **INTERMEDIATE AND FINISH COAT:** Rough surface: approx. 110-220ml/m² of product.
Smooth surface: approx. 90-220ml/m².

7. STORAGE: Store the product in a frost-free location where it is protected from the weather and away from direct sunlight.

* Coverage areas are provided for information only and can be used to assess a project. They are in no way contractual; only tests can define the actual amount of product required depending on the surface to be treated.

PHYSICOCHEMICAL PROPERTIES

- | | |
|--|--|
| <ul style="list-style-type: none">• Dry film thickness: approx. 30µ/100 ml/m².• Water permeability coefficient: 15-150g/m²*d on average• Density at 1.00g ± 0.03g/cm³ at 20°C | <ul style="list-style-type: none">• Dry extract by weight: approx. 34• VOC: <1 g/L |
|--|--|

APPLICATION PRECAUTIONS

1. PROTECTION OF SURFACES: Protect surfaces not to be treated (glass, PVC, etc.).

2. PROTECTION OF PERSONNEL: Contains 1,2-benzisothiazol-3(2H)-one 2-methyl-2H-isothiazole-3-one. Wear gloves and protective equipment when using: waterproof overalls, PVC gloves; for spray application: helmet with protective visor; for roller application: protective goggles. In case of irritation or rash, wash with plenty of water and seek medical advice.

Important: The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand. See the Safety Data Sheet (SDS).



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.

Technical Data Sheet • May 2023
Page 2/2